

Model	G1000i	G2000i
Picture		
Rated frequency (Hz)	50/60HZ	50/60HZ
Rated voltage (V)	230V	230V
Rated output (KW)	0.85kw	1.7kw
Max. output (KW)	0.95kw	1.9kw
DC output	12V-6A	12V-6A
Phase number	Single	Single
Carte d'allumage	CDI	CDI
Engine	4 stroke, OHC single cylinder	4 stroke, OHC single cylinder
Cylinder	43.5*36mm	60*40mm
Displacement	53.2cc	113cc
Compression	7.6	9.1
Rated speed	4800rpm	4200rpm
Stator/Motor	AC brushless	AC brushless
Structural type	Portable	Portable
Fuel capacity (L)	2.1L	3.5L
Set fuel consumption (g/kw.h)	395g/kw.h	395g/kw.h
Continuous running time (hr) (rated output)	3.5H	3.7H
Noise level (zero load--full load) dB (A)/7m	64db	64db
Overall dimension(L×W×H) (mm)	Ti/Tc: 505*280*410	Ti/Tc: 555*305*460
Net weight (kg)	15/15.3kg	24/25kg
Starting system	Recoil starter	Recoil starter
Lube oil type	CD grade or SAE10W30, 15W40	CD grade or SAE10W30, 15W40
Fuel type	Automotive unlead gasoline	Automotive unlead gasoline
Certificates	CSA,CE,EPA, EMC	CSA,CE,EPA, EMC